



2k x 2k Side-Mounted TEM CCD Camera Solution






Diffraction image of aluminium



Liver cell-nucleus



Dislocations in a low-angle grain-boundary (aluminium)

VELETA - 2K X 2K SIDE-MOUNTED TEM CCD CAMERA SOLUTION

The Veleta is a side-mounted TEM camera offering a Peltier-cooled CCD chip with 2k x 2k pixels and a dynamic range of 14 bits. The Veleta reflects current life science, bio-medicine, materials science and industrial requirements. This new camera works perfectly in conjunction with our tomography software, iTEM Solution Tomography. The Veleta is another component of Olympus Soft Imaging Solution's vision of "Electron Microscopy made simple."

The pneumatically driven Veleta can be mounted onto the wide-angle (35 mm) port of almost all common TEMs. With attributes such as an optimized scintillator and a highly sensitive chip, this camera system guarantees high dynamic range and high sensitivity. Even weak signals can be recorded. Frame rates of more than 20 frames per second at binning 4 make it viable to search and focus directly onscreen. A Fire-Wire™ interface is used for transferring data from camera to PC. The Veleta is fully integrated into iTEM, the TEM imaging platform. This means that the acquired images can be processed, evaluated, archived and documented - immediately and at the greatest of convenience.

Customized adapters

The camera system consists of a high yield phosphor screen, a prism to reflect the image onto the CCD sensor, as well as housing and a flange specific to each TEM. The rigidly coupled phosphor scintillator-lens-CCD combination is a fundamental prerequisite for ensuring optimum conditions for artifact-free shading correction. The positioning of the phosphor screen inside the TEM is pneumatically driven. X-ray safety is guaranteed up to 200 KeV.

Special lens

In a partnership with lens makers of the highest caliber, the Veleta camera system is equipped with a new specially-designed lens. In conjunction with its state-of-the-art CCD chip and even more efficient scintillators, the custom optics of the Veleta system ensures much greater sensitivity and light efficiency, as well as a signal-to-noise ratio higher than ever before.

CCD chip

The highly sensitive CCD chip used in the camera system provides a maximum resolution of 2048 x 2048 pixels with a 14-bit dynamic range. In conjunction with further dark-current-reduction measures, this increases detection efficiency of the entire camera system. The CCD sensor has uniquely high quantum efficiency that when combined with reduced dark current results in a tremendous increase of the camera system's total detection quantum efficiency (DQE).

CCD Cooling

Noise – known as "dark current" – is generally introduced into an image if the CCD chip is not cooled to a sufficiently low temperature. This effect is not a problem with the Veleta due to its sophisticated Peltier-cooling system. The temperature of the CCD chip is regulated at 10° C (@ 25° C ambient temperature). Noise is further suppressed by highly efficient read-out technology.

High frame rates

Frame rates of more than 20 images per second at binning 4 and of 5 images per second at full resolution are supported. Such high frame rates are ideal for locating suitable sample segments directly onscreen. In conjunction with the RTFFT (Real Time Fast Fourier Transformation), the focusing mode offers ideal assistance for setting various microscope parameters. This enables you to conveniently focus your

Features

Up to 2048 x 2048 pixels

Peltier cooled

Lens coupled

14-bit

Applications

Tomography

Diffraction

Materials Science

Virology

Pathology

Digital Documentation

sample on your PC screen as opposed to having to use the viewing screen of the microscope. No matter what mode you select, the Veleta offers excellent dynamic range and high sensitivity.

Binning

Binning modes help to increase camera sensitivity even more. The Veleta supports several binning modes: 2x, 4x and up to 8x.

Variable exposure times

The interline chip has an electronic shutter. The Veleta offers exposure times ranging from 100 μ s to 160 s. This makes it possible to acquire images of intense illumination or of very low intensity.

High sensitivity

The Veleta's high sensitivity means samples can be observed on the monitor at beam intensities so low, users would usually not be able to see anything on the TEM viewing screen.

Anti-Blooming / Diffraction

The CCD chip's interline-transfer architecture guarantees high anti-blooming. Individual pixels are clearly delineated using the Veleta. In conjunction with extremely short exposure times, this optimizes the acquisition of diffraction images.

Optimized scintillators

The Veleta uses optimized and highly sensitive phosphor scintillators. In order to match customers' individual demands various scintillators can be customized to handle multiple accelerating voltages and applications.

FireWire™ technology

Data is transferred from the camera to the PC via FireWire™ (IEEE1394) interface. This technology means the Veleta can be installed on any PC or laptop equipped with a FireWire™ port. No additional special frame grabber is necessary.

Real-time functions

Integration of the camera with iTEM, the Olympus Soft Imaging Solutions TEM imaging platform, ensures real-time shading correction, intensity histograms, auto contrast adjustment and real-time Fast Fourier Transformation during image acquisition.

Integration

The integration of the Veleta with iTEM provides professional functions such as auto-focus, labeling, processing, archiving, analyzing and report generation. Photographic quality printouts are available in seconds after acquisition.

Ideal for tomography



The Veleta works perfectly in conjunction with our tomography software, iTEM Solution Tomography.

D Veleta

2k x 2k side-mounted TEM camera

**E Field of View**

Frame shows Veleta's field of view within TEM fluorescence screen



Muscle cell of a worm

Specifications

G Veleta


Chip type	16.67 x 16.67 mm interline CCD image sensor
Resolution (pixels)	2048 x 2048
Binning 2x (pixels)	1024 x 1024
Pixel size (µm ²)	7.4 x 7.4
Effective pixel size (µm ²)	13.1 x 13.1
Binning	2x, 4x and 8x
Pixel clock rate (MHz)	24.6
Frame rate (fps)	5 @ full resolution (14 bit)
Frame rate (fps)	> 20 @ binning 4
Digitization (bit)	14
Exposure time	100 µs - 160 s
Display	Full image in real time
Chip temperature	10° C @ 25° C ambient temperature
Noise reduction	Correlated double sampling
Camera mount	on wide angle port
Camera positioning	PC controlled pneumatic movement / control box
Anti blooming	> 300x
PC interface	FireWire™ (IEEE 1394)
Camera coupling	Lens-optically coupled
Trigger Option	Yes
Partial Readout	Yes
Full Well Capacity (e ⁻)	40000
Dark Current (e ⁻ /p/s)	~ 40
Readout Noise (e ⁻)	< 20
Scintillator	Highly sensitive phosphor optimized for accelerating voltages of 100 keV / 200 keV
CE certified	Yes
RoHS compliant	Yes

G Veleta

2k x 2k side-mounted TEM CCD camera



System Diagram



Specifications are subject to change without any obligation on the part of the manufacturer.
Soft Imaging System is a trademark of Olympus Soft Imaging Solutions GmbH.

www.olympus-sis.com
www.soft-imaging.net

OLYMPUS

OLYMPUS SOFT IMAGING SOLUTIONS GMBH

Johann-Krane-Weg 39
48149 Münster
Germany
Phone: +49 (251) 79800-0
Fax: +49 (251) 79800-6060
info.osis@olympus-sis.com

OLYMPUS SOFT IMAGING SOLUTIONS CORP.

12596 West Bayaud Ave., Suite 300
Lakewood, CO 80228
USA
Phone: +1 (303) 234-9270
Fax: +1 (303) 234-9271
info.osis@olympus-sis.com

OLYMPUS SOFT IMAGING SOLUTIONS PTE. LTD.

No. 2 Jurong East Street 21 #05-30,
IMM Building, Singapore 609601
Singapore
Phone: +65 (6777) 7898
Fax: +65 (6777) 7218
info.osis@olympus-sis.com